

# The ltdocinit module

The L<sup>A</sup>T<sub>E</sub>X Project\*

Version 0.95k, released 2022-01-28

## 1 ltdocinit documentation

This small module defines `\DocumentMetadata` and the older alias `\DeclareDocumentMetadata` and the related keys. It also defines commands to store document properties in a global container.

When the kernel will provide `\DocumentMetadata` directly this module will slowly disappear.

### 1.1 `\DocumentMetadata`/`\DeclareDocumentMetadata`

---

<code>\DocumentMetadata</code>	<code>\DocumentMetadata{&lt;key-value list&gt;}</code>
<code>\DeclareDocumentMetadata</code>	<code>\DeclareDocumentMetadata{&lt;key-value list&gt;}</code> (deprecated)

---

Currently there is no dedicated location to declare settings concerning a document as a whole. Settings are placed somewhere in the preamble or with the class options or even with some package options. For some settings this can be too late, for example the pdf version can no longer be changed if a package has used code which already opened the PDF.

`\DocumentMetadata` as a new command should unify such settings in one place. It should be used before `\documentclass`. `\DocumentMetadata` can be used more than once.

With a L<sup>A</sup>T<sub>E</sub>X 2022-06-01 or newer (currently provided as `latex-dev`) the command is provided by the kernel and will load the pdfmanagement, with older L<sup>A</sup>T<sub>E</sub>X the pdfmanagement must be loaded first manually with `\RequirePackage{pdfmanagement-testphase}`.

The keys defined for `\DocumentMetadata` currently allows to set the PDF version, to set the PDF `/Lang`, to uncompress a pdf, to set the language and to declare a few PDF standards and to load some colorprofiles.

`\DocumentMetadata` is also used to activate the new PDF management code and it loads a number of required files for the PDF management code. As this forces the loading of the backend files, a backend which can't be detected automatically like `dvipdfmx`, must be set in the first `\DocumentMetadata`.

Currently the following keys are implemented

**backend** Passes the backend name to expl3. This is needed only if the needed backend can't be automatically determined or if the workflow used requires a special backend.

---

\*E-mail: [latex-team@latex-project.org](mailto:latex-team@latex-project.org)

**pdfversion** Sets the PDF version explicitly, e.g., `pdfversion=1.7`

**uncompress** (no value) Forces an uncompressed pdf — mainly for debugging purposes.

**lang** Explicitly sets the Lang entry in the Catalog, e.g., `lang=de-DE`. If not given the default value used is `en-US`.

**pdfstandard** Choice key to set the pdf standard. Currently `A-1b`, `A-2a`, `A-2b`, `A-2u`, `A-3a`, `A-3b` and `A-3u` are accepted as values. The casing is irrelevant, `a-1b` works too. The underlying code to ensure the requirements (as far as they can be ensured) is still incomplete, but a color profile is included and the `/OutputIntent` is set. The `u` variants for example do not force unicode, but they will pass the information to `hyperref` and `hyperxmp`. The `a` variants do *not* enforce (or even test) a tagged pdf yet. More information can be found in the documentation of `l3pdfmeta`.

**colorprofiles** This allows to load icc-colorprofiles. Details are described in the documentation of `l3pdfmeta`.

**testphase** This key is used to load testphase code. The values it accepts and their effect will change over time, when testphase packages are added or removed or when the code is moved into the kernel.

**phase-I** This value loads code implementing the first phase of the project [1], i.e., it will load the `tagpdf` package. It will also activate tagging by issuing `\tagpdfsetup{activate,interwordspace}`. This phase is frozen.

**phase-II** This is the current development phase. Currently it differs from **phase-I** only in one point: It will additionally activate tagging of paragraphs with `\tagpdfsetup{paratagging}`. In the upcoming months it will also enable automatic tagging of other basic document elements.

The **testphase** key can only be used in the first `\DocumentMetadata`.

**debug** This key activates some debug options. It takes a list of key-values as value. Currently the following keys are known:

**para** with the default and only value `show`. It will activate the `paratagging-show` option of `tagpdf`,

**log** with the values as described in the documentation `tagpdf`,

**uncompress** which does the same as **uncompress** as main key

**pdfmanagement** a boolean which allows to deactivate the pdfmanagement.

**firstaidoff** This accepts a comma lists of keywords and disables the patches related to them. More information can be found in the documentation of `pdfmanagement-firstaid`.

## 1.2 Container for document properties

The module provides a container where classes, packages and users can store properties of the document which are perhaps of interest or use for other packages or the author.

The properties are stored with a key `label/property`. The values can be retrieved expandably.

<hr/> <code>\AddToDocumentProperties</code> <hr/>	<code>\AddToDocumentProperties[\langle label \rangle]{\langle property \rangle}{\langle value \rangle}</code> <p>This stores <math>\langle value \rangle</math> under the key <math>\langle label \rangle / \langle property \rangle</math>. By default <math>\langle label \rangle</math> is the current package name <code>\@currname</code>. If another label is chosen, it should be one which avoids clashes with other packages using the container. The label <code>document</code> is reserved.</p>
<hr/> <code>\GetDocumentProperties</code> <hr/>	<code>\GetDocumentProperties{\langle label / property \rangle}</code> <p>Expands to the <math>\langle value \rangle</math> corresponding to <math>\langle label / property \rangle</math> in the container. If <math>\langle label / property \rangle</math> is missing, this has an empty expansion. The result is returned within <code>\exp_not:n</code>, which means that the <math>\langle value \rangle</math> does not expand further when appearing in an x-type argument expansion.</p>
<hr/> <code>\ShowDocumentProperties</code> <hr/>	<code>\ShowDocumentProperties</code> <p>This show the current content of the container.</p>

## References

- [1] Frank Mittelbach and Chris Rowley: *L<sup>A</sup>T<sub>E</sub>X Tagged PDF — A blueprint for a large project*. <https://latex-project.org/publications/indexbyyear/2020/>

## 2 ltdocinit implementation

```

1 <@@=pdfmanagement>
2 <*header>
3 \ProvidesExplPackage{ltdocinit}{2022-01-28}{0.95k}
4   {Initialize document metadata}
5 </header>

```

`\DocumentMetadata` will be defined by the kernel in short time. So we define it and the keys here only if it is not already defined.

### 2.1 The keys for `\DocumentMetadata`

We define the keys first so that we can test if `\DocumentMetadata` exist (testing for the format date would be nice but would fail for the current latex-dev).

<code>\g__pdfmanagement_firstaidoff_clist</code>	<p>A list to store the firstaid code which should be disabled</p> <pre> 6 &lt;*package&gt; 7 \clist_new:N \g__pdfmanagement_firstaidoff_clist </pre> <p>(End definition for <code>\g__pdfmanagement_firstaidoff_clist</code>.)</p>
<code>\g__pdfmanagement_testphase_tl</code>	<p>a tl to store the testphase loading code so that we can load them at the end of the command.</p> <pre> 8 \tl_new:N \g__pdfmanagement_testphase_tl </pre> <p>(End definition for <code>\g__pdfmanagement_testphase_tl</code>.)</p> <pre> 9 \cs_if_free:NT \DocumentMetadata 10 { 11   \keys_define:nn { document / metadata } 12   { 13     backend .choices:nn = </pre>

```

14         { dvipdfmx , dvips , dvisvgm , luatex , pdftex , pdfmode , xdvipdfmx , xetex }
15     {
16         \sys_load_backend:n {#1}
17     },
18     backend .groups:n = { init } ,
19 }
20
21 \keys_define:nn { document / metadata }
22 {
23     ,pdfversion .code:n =
24     {
25         \pdf_version_gset:n { #1 }
26         \AddToDocumentProperties[document]{pdfversion}{#1}
27     }
28     ,uncompress .code:n =
29     {
30         \pdf_uncompress:
31     }
32     ,uncompress .value_forbidden:n = true
33     ,lang .code:n =
34     {
35         \pdfmanagement_add:nnn {Catalog} {Lang}{#{1}}
36         \AddToDocumentProperties[document]{lang}{#1}
37     }
38     %,xmpmeta .bool_gset:N = \g_pdfmeta_xmp_bool %see pdfmeta unused and undefined for now
39     % this uses internal command from pdfmeta, it should probably move there ...
40     ,pdfstandard .code:n =
41     {
42         \exp_args:Nnx
43         \keys_set:nn {document / metadata} {_pdfstandard=\str_uppercase:n{#1}}
44     }
45     ,_pdfstandard .choices:nn =
46     {A-1B,A-2A,A-2B,A-2U,A-3A,A-3B,A-3U}
47     {
48         \prop_if_exist:cT { g__pdfmeta_standard_pdf/#1_prop }
49         {
50             \prop_gset_eq:Nc \g__pdfmeta_standard_prop { g__pdfmeta_standard_pdf/#1_prop }
51         }
52         \AddToDocumentProperties [document]{pdfstandard}{#1}
53     }
54     ,_pdfstandard / unknown .code:n =
55     {
56         \msg_warning:nnn{pdf}{unknown-standard}{#1}
57     }
58     ,testphase .multichoice:
59     ,testphase / tagpdf .code:n =
60     {
61         \tl_gput_right:Nn\g__pdfmanagement_testphase_tl
62         {
63             \file_if_exist_input:nF {tagpdf-latex-lab-testphase.ltx}
64             {
65                 \RequirePackage{tagpdf}
66                 \AddToDocumentProperties [document]{testphase/tagpdf}{loaded}
67                 \tagpdfsetup{activate,paratagging,interwordspace}

```

```

68         \AddToDocumentProperties [document]{tagging}{active}
69         \AddToDocumentProperties [document]{tagging/para}{active}
70         \AddToDocumentProperties [document]{tagging/interwordspace}{active}
71     }
72 }
73 }
74 ,testphase / unknown .code:n =
75 {
76     \tl_gput_right:Nn\g__pdfmanagement_testphase_tl
77     {
78         \file_if_exist_input:nF {#1-latex-lab-testphase.ltx}
79         {
80             \msg_warning:nnn{document}{latex-lab-pkg-missing}{#1}
81         }
82     }
83 }
84 ,activate .multichoice:
85 ,activate / tagging .code:n =
86 {
87     \PackageWarning{pdfmanagement-testphase}
88     {The~activate~key~is~deprecated.\MessageBreak
89     Tagging~is~activated~with~'testphase=tagpdf'~directly}{#1}
90 }
91 ,debug .code:n =
92 {
93     \keys_set:nn { document / metadata / debug } {#1}
94 }
95 ,debug / para .code:n =
96 {
97     \AddToHook
98     {
99         package/tagpdf/after
100     }
101     {
102         \tagpdfsetup{paratagging-show}
103     }
104 }
105 ,debug / log .code:n =
106 {
107     \AddToHook
108     {
109         package/tagpdf/after
110     }
111     {
112         \tagpdfsetup{log=#1}
113     }
114 }
115 ,debug / uncompress .code:n =
116 {
117     \pdf_uncompress:
118 }
119 ,debug / pdfmanagement .bool_gset:N = \g__pdfmanagement_active_bool
120 ,debug / firstaidoff .clist_gset:N = \g__pdfmanagement_firstaidoff_clist
121 }

```

```
122 }
```

## 2.2 \DocumentMetadata/\DeclareDocumentMetadata

At first we have to define the older alias `\DeclareDocumentMetadata` if `\DocumentMetadata` is already defined in a newer LaTeX version. Here we load the latex-lab support (if it hasn't been loaded before) and redefine then `\DeclareDocumentMetadata` to `\DocumentMetadata`

```
123 \cs_if_exist:NT \DocumentMetadata
124 {
125   \cs_new_protected:Npn \DeclareDocumentMetadata
126   {
127     \cs_if_free:NT \DocumentMetadata
128     {
129       \file_if_exist_input:nF {documentmetadata-support.ltx}%
130       {
131         \@latex@error
132         {No~support~files~for~\noexpand\DeclareDocumentMetadata~found}
133         {
134           Is~the~'LaTeX-lab'~bundle~installed?
135           \MessageBreak
136           Without~it,~the~declaration~is~ignored.
137         }
138         \let\DeclareDocumentMetadata\@gobble
139       }
140     }
141     \RenewDocumentCommand \DeclareDocumentMetadata {}
142     { \DocumentMetadata }
143     \DocumentMetadata
144   }
145 }
```

Now we provide a definition for `\DocumentMetadata` if it doesn't exist yet.

```
146 \cs_if_free:NT \DocumentMetadata
147 {
```

`\DocumentMetadata` should for now not be used after `\documentclass` so we error in this case. It can be used more than once but follow-up calls should not do the initialization code.

```
148   \prop_gput:Nnn \g_msg_module_type_prop { document } { LaTeX }
149   \prop_gput:Nnn \g_msg_module_name_prop { document } { DocumentMetadata }
150   \msg_new:nnn
151   { document } { setup-after-documentclass }
152   {
153     \token_to_str:N \DocumentMetadata \c_space_tl
154     should~be~used~only~before~\token_to_str:N\documentclass
155   }
156   \msg_new:nnn
157   { document } { latex-lab-pkg-missing }
158   {
159     LaTeX-lab~package~'#1'~not~found.
160   }
```

## `\DocumentMetadata`

```
161 \NewDocumentCommand\DocumentMetadata { m }
162 {
163   \cs_if_eq:NNTF \documentclass \@twoclasseserror
164   { \msg_error:nn { document } { setup-after-documentclass } }
165   {
```

The wanted backend must be detected first, we read the init key and then force the loading by loading expl3. The backend can contains management commands, so the boolean should be set to true first.

```
166     \bool_gset_true:N \g__pdfmanagement_active_bool
167     \keys_set_groups:nnn { document / metadata } { init } { #1 }
168     %if no backend has been loaded force it now:
169     \str_if_exist:NF \c_sys_backend_str
170     {
171       \sys_load_backend:n {}
172     }
```

Now we load the extra backend code

```
173     \ExplSyntaxOn\makeatletter
174     \file_input:n {l3backend-testphase-\c_sys_backend_str.def}
175     \ExplSyntaxOff\makeatother
```

set the default language, process the rest of the keys, and setup the generic driver

```
176     \keys_set_filter:nnn { document / metadata } { init } { lang=en-US, #1 }
177     \bool_if:NT \g__pdfmanagement_active_bool
178     {
179       \PassOptionsToPackage{customdriver=hgeneric-testphase}{hyperref}
180     }
```

`\pdfmanagement_add:nnn` has collected values in this hook.

```
181     \hook_use_once:n {pdfmanagement/add}
```

Redefine `\DocumentMetadata` so that it only process the keys. We need to update the `hyperref` option if the active status changes.

```
182     \RenewDocumentCommand\DocumentMetadata { m }
183     {
184       \keys_set_filter:nnn { document / metadata } { init } { ##1 }
185       \bool_if:NTF \g__pdfmanagement_active_bool
186       {
187         \str_remove_all:cn
188         {opt@hyperref.sty}{customdriver=hgeneric-testphase}
189         \PassOptionsToPackage
190         {customdriver=hgeneric-testphase}{hyperref}
191       }
192       {
193         \str_remove_all:cn
194         {opt@hyperref.sty}{customdriver=hgeneric-testphase}
195       }
196     }
```

Load more modules, the testphase code and the firstaid code.

```
197     \g__pdfmanagement_testphase_tl
198     \RequirePackage{pdfmanagement-firstaid}
199   }
200 }
```

At last we need to provide the older alias here too

```
201 \NewDocumentCommand\DeclareDocumentMetadata{}{\DocumentMetadata}  
202 }
```

(End definition for \DocumentMetadata. This function is documented on page 1.)

## 2.3 Container for document Properties

The container for the document properties is a prop

\g\_\_pdfmanagement\_documentproperties\_prop

```
203 \prop_new:N \g__pdfmanagement_documentproperties_prop %
```

(End definition for \g\_\_pdfmanagement\_documentproperties\_prop.)

### \AddToDocumentProperties

```
204 \NewDocumentCommand\AddToDocumentProperties{0{\@currname}mm}  
205 {  
206   \exp_args:NNx  
207   \prop_gput:Nnn \g__pdfmanagement_documentproperties_prop  
208   {  
209     \tl_if_blank:eTF {#1}{top-level/}{#1/} #2  
210   }  
211   { #3}  
212 }
```

(End definition for \AddToDocumentProperties. This function is documented on page 3.)

### \GetDocumentProperties

```
213 \NewExpandableDocumentCommand\GetDocumentProperties{m}  
214 {  
215   \prop_item:Nn \g__pdfmanagement_documentproperties_prop {#1}  
216 }
```

(End definition for \GetDocumentProperties. This function is documented on page 3.)

### \ShowDocumentProperties

```
217 \msg_new:nnn { pdfmanagement } { show-properties }  
218 {  
219   The~following~document~properties~have~been~stored:  
220   #1  
221 }  
222 \NewDocumentCommand\ShowDocumentProperties {}  
223 {  
224   \msg_show:nnx {pdfmanagement}{show-properties}  
225   {  
226     \prop_map_function:NN \g__pdfmanagement_documentproperties_prop \msg_show_item:nn  
227   }  
228 }
```

(End definition for \ShowDocumentProperties. This function is documented on page 3.)

```
229 \endpackage
```



# Index

The italic numbers denote the pages where the corresponding entry is described, numbers underlined point to the definition, all others indicate the places where it is used.

<b>A</b>		\keys_set:nn ..... 43, 93
\AddToDocumentProperties .....		\keys_set_filter:nnn ..... 176, 184
..... 3, 26, 36, 52, 66, 68, 69, 70, <u>204</u>		\keys_set_groups:nnn ..... 167
\AddToHook .....		
97, <u>107</u>		
<b>B</b>		<b>L</b>
bool commands:		\let ..... 138
\bool_gset_true:N .....	166	
\bool_if:NTF .....	177, 185	<b>M</b>
<b>C</b>		\makeatletter ..... 173
clist commands:		\makeatother ..... 175
\clist_new:N .....	7	\MessageBreak ..... 88, 135
cs commands:		msg commands:
\cs_if_eq:NNTF .....	163	\msg_error:nn ..... 164
\cs_if_exist:NTF .....	123	\g_msg_module_name_prop ..... 149
\cs_if_free:NTF .....	9, 127, 146	\g_msg_module_type_prop ..... 148
\cs_new_protected:Npn .....	125	\msg_new:nnn ..... 150, 156, 217
		\msg_show:nnn ..... 224
		\msg_show_item:nn ..... 226
		\msg_warning:nnn ..... 56, 80
<b>D</b>		
\DeclareDocumentMetadata .....		<b>N</b>
..... 1, 6, 125, 132, 138, 141, 201		\NewDocumentCommand ... 161, 201, 204, 222
\documentclass .....	1, 6, 154, 163	\NewExpandableDocumentCommand ..... 213
\DocumentMetadata .....	1–3, 6,	\noexpand ..... 132
7, 9, 123, 127, 142, 143, 146, 153, <u>161</u>		
<b>E</b>		<b>P</b>
exp commands:		\PackageWarning ..... 87
\exp_args:NNx .....	206	\PassOptionsToPackage ..... 179, 189
\exp_args:Nnx .....	42	pdf commands:
\exp_not:n .....	3	\pdf_uncompress: ..... 30, 117
\ExplSyntaxOff .....	175	\pdf_version_gset:n ..... 25
\ExplSyntaxOn .....	173	pdfmanagement commands:
		\pdfmanagement_add:nnn ..... 7, 35
<b>F</b>		pdfmanagement internal commands:
file commands:		\g__pdfmanagement_active_bool ...
\file_if_exist_input:nTF . 63, 78, 129		..... 119, 166, 177, 185
\file_input:n .....	174	\g__pdfmanagement_documentproperties_
		prop ..... <u>203</u> , 207, 215, 226
<b>G</b>		\g__pdfmanagement_firstaidoff_
\GetDocumentProperties .....	3, <u>213</u>	clist ..... <u>6</u> , 120
		\g__pdfmanagement_testphase_tl ..
<b>H</b>		..... <u>8</u> , 61, 76, 197
hook commands:		pdfmeta commands:
\hook_use_once:n .....	181	\g_pdfmeta_xmp_bool ..... 38
<b>K</b>		pdfmeta internal commands:
keys commands:		\g__pdfmeta_standard_prop ..... 50
\keys_define:nn .....	11, 21	prop commands:
		\prop_gput:Nnn ..... 148, 149, 207
		\prop_gset_eq:NN ..... 50

